

### Highlights:

- Parallel & separable wires
- 13 AWG thin and dense stranded conductors
- Color coded polarity identification

### Product information:

The RZ series cables are parallel designed loudspeaker cables with a maximum flexibility and strength. They are mostly used for indoor applications. Each conductor is fitted with a highly flexible PVC jacket. The two parallel conductors are in black colour and one of the two has a thin red line to identify the polarity. The RZ series cables are "all-round" loudspeaker cables suited for all kinds of applications on loudspeaker level.



### Inner Conductors:



### Product Features:

Application	AV & IT
Series	Bulk & Accessories

### Physical Characteristics:

Type of cable	2-core loudspeaker cable	
Inner conductor	Material	BC 30 x 7 x 0.12 mm (Ø) (OFC)
	Section	2.5 mm <sup>2</sup>
	Number of conductors	2
	American Wire Gauge	13 AWG
Outer jacket	Material	Flexible PVC 4 x 8 mm (Ø)
	Colours	Black with red molded line

## Mechanical Characteristics:

---

Temperature range Fixed installation - 40 °C till + 80 °C

Mobile installation - 25 °C till + 70 °C

Bending radius Fixed installation 8 x outer diameter

Mobile installation 10 x outer diameter

## Electrical Characteristics:

---


Capacitance Cond/Cond 118 pF / m @ 1 kHz

Lead resistance 0.9 Ω / 100 m

Cable Crosstalk Min. 74 dB / 100 m

## Cross sections:

---



## Variants:

---

- RZ25/1 - 100 meter